



FOUNDATIONS:
 CONCRETE TO BE CAST A MINIMUM OF 7 DAYS BEFORE INSTALLATION OF EQUIPMENT.
 (GRADE C32/40 - 20mm GRAVEL)
 FOUNDATIONS SHOULD BE SMOOTH, FLAT AND LEVEL WITH EACH OTHER

ELECTRICAL SPECIFICATION:
 VOLTAGE (V) : 230
 FREQUENCY (Hz) : 50
 LOAD CURRENT (A) : 6
 RATING (Kw) : 0.37
 DUTY RATING: 100%

OPTIONAL ACCESSORIES:
 PVC / ALUMINIUM CURTAIN (FULL/ HALF)
 STOP SIGNS
 BOOM LIGHTS
 TIP SUPPORT POST

±1.0mm UOS	Finish AS PER CONTRACT		
DESIGNED BY J.DAVIS	MATERIAL AS PER CONTRACT	DATE 15/02/2013	
NEWGATE (NEWARK) LTD BRUNEL DRIVE, NEWARK, NOTTS. NG24 2DE TELEPHONE 01636 700172 EMAIL SALES@NEWGATE.UK.COM		TITLE LAYOUT - AUTOMATIC BARRIER (UP TO 9.0m)	
PART No 104/3/37367		ISSUE A	SHEET 1/ 1